



SPO10 SERIES TWO POST LIFTS

10,000 lbs. CAPACITY / SYMMETRIC LIFTS

Trust the industry standard symmetrical two post lift.

For over 30 years, Rotary Lift has built quality into every two-post we've designed. With industry-leading features, the SPO10 delivers everything your shop needs.

Choose your:

- Arm configuration and adapter type
- Lift height • Power option and accessories

SYMMETRIC LIFT SPECIFICATIONS

*WITH SHOCKWAVE

Overall Height: 11' 8-1/2" / 12' 4-1/2"

Overall Width: 11' 5-5/8"

Drive-thru: 102 1/2"

Inside Columns: 114 3/4"

Min. Bay Size: 12' x 24'

Ceiling Height Min: 12' / 12' 6"

Motor / Voltage 1Ø: 2 HP, 208-230V / 5 HP, 110V*

Time of Full Rise and Descent: 45 seconds / 40 seconds
25 seconds / 19 seconds*

* Actual rise and descent times vary depending on vehicle weight.



MODEL SHOWN:
SPO10N700BL



MODEL SHOWN:
SPO10N800BL

SPO10 TRIO™

Includes TRIO™ 2-piece, three-stage arms with exclusive FA three-position adapters



SPO10

Standard 2-stage arms with exclusive three-position flip-up FA adapters



Flip-up adapters feature great strength in a simple design.

The entire assembly is joined with a single pin providing stable support in any position.

Select product photography is shown with optional accessories that are not standard with each lift purchase.

SPO10 SERIES LIFTS

ARE AVAILABLE WITH SHOCKWAVE-EQUIPPED POWER

SHOCKWAVE™ DC power with onboard 110v charger provides 2X the lifting speed of conventional lifts.



SCAN THIS VIDEO CODE TO LEARN ABOUT THE BENEFITS OF ROTARY SHOCKWAVE LIFTS

Rotary Lift

2700 Lanier Drive / Madison, IN 47250, USA

rotarylif.com

Lit# Rotary SPO10 Cutsheet.2021.11

©2021 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

SYMMETRIC LIFT MODELS

BL = Blue / RD = Red

CONVENTIONAL 2-STAGE ARMS

Flip Up Adapters (FA)

THREE-STAGE TRIO ARMS

Flip Up Adapters (FA)

CONVENTIONAL 3-STAGE ARMS

Truck Adapters (TA)

CONVENTIONAL 3-STAGE ARMS

Round Adapters (RA)

	STANDARD	SPO10N700BL SPO10N700RD	SPO10N800BL SPO10N800RD	SPO10N5T0BL SPO10N5T0RD	SPO10N5G0BL SPO10N5G0RD
	SHOCKWAVE EQUIPPED	SPO10U705BL SPO10U705RD	SPO10U805BL SPO10U805RD	SPO10U5T5BL SPO10U5T5RD	SPO10U5G5BL SPO10U5G5RD
Rise*	STANDARD SHOCKWAVE	72 5/8" - 78 1/8" 75 5/8" - 81 1/8"	72 3/4" to 78 1/4" 75 3/4" to 81 1/4"	72 11/16" to 75 3/16" 75 11/16" to 78 3/16"	72 1/2" to 74 3/4" 75 1/2" to 77 3/4"
Front Arm Min/Max		31" - 54"	30 1/2" - 54 7/8"	27 1/2" / 59"	27 1/2" / 59"
Rear Arm Min/Max		31" - 54"	30 1/2" - 54 7/8"	27 1/2" / 59"	27 1/2" / 59"
Min Adapter Height		4 5/8"	4 3/4"	4 11/16"	4 1/2"

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke. Heights and widths reflect standard settings.
** Actual rise and descent times vary depending on vehicle weight. SPO10 lift colors come standard with your choice of red or blue.

North / South America Information

Sales: 800.445.5438
insidesales@rotarylif.com

Tech. Support: 800.445.5438
technicalsupport@rotarylif.com

Government Sales: 800.445.5438 X5655

For additional information: rotarylif.com/Government-Purchasing-Assistance/

Global Contact Information

USA: 1.812.273.1622

Canada: 1.905.812.9920

Latin America / Caribbean: 1.812.273.1622

Brazil: +55.11.4534.1995

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.



SPO10 TA

3-stage conventional arms with thread-up padded TA adapters. Optional SHOCKWAVE™ power available.

TA adapters are frame-engaging padded polymer adapters that thread-up for additional adapter reach.

SPO10 RA

3-stage conventional arms with thread-up padded RA adapters. Optional SHOCKWAVE™ power available.

RA adapters are round padded polymer adapters that thread-up for additional positioning.

